

Urovo

DT66

Enterprise Mobile Computer

- 6.5-inch ultra-high-definition (720*1600) thin-bezel display, offers more information at one page and less scrolling.
- Supports in-display and backside NFC reading to meet diverse usage needs.
- The 5000mAh smart battery with a built-in battery management system enhancing overall battery life. With the hot swap feature, it achieves uninterrupted 24-hour operation.
- Powered by the latest Qualcomm 2.4GHz high-performance processor, it delivers exceptional processing speed, further empowering faster decoding of 1D/2D/DPM barcode.
- Wi-Fi 6E and 5G delivers the super fast and reliable wireless connections.
- Optional iToF camera for three-dimensional volume measurement of parcel.



2.4GHz
Processor



Android 13
O.S.



IP68
Sealing



6.5-inch
Display



5000mAh
Smart Battery

Optional Accessories:



Trigger
Handle



4-Slot Battery
Charging Cradle



Charging
Cradle

DT66 Enterprise Mobile Computer

Specifications

UROVO



Processor

Octa-core 2.4 GHz



O.S.

Android 13,
upgradable to Android 18
Support GMS/AER



Memory

RAM: 4GB ROM: 64GB
RAM: 8GB ROM: 128GB (optional)
Micro-SD card, Up to 256 GB



Display

6.5 inch display,
720*1600



Touch Screen

Ultra sensitive capacitive touch panel,
support multi-touch, works with gloves
and wet fingers



Dimensions

175.8 mm L x 76.5 mm W x
14.5 mm D
Weight: About 283g



Scanning

Professional scan engine
Support international standard
1D/2D barcode;
Support barcode displayed on
screen



Camera

Front: 5MP FF;
Rear: 13MP PDAF
Optional iToF camera



Sensors

Light + Accelerator+ Proximity +
Geomagnetic + Gyro+
Pressure(optional)



Audio

Dual-Microphone with noise cancellation,
1.5W speaker for loud noise,
receiver supports echo cancellation



Battery

Capacity: 3.85V 5000mAh
Support hot swap



Buttons

PWR button
Vol +/- button
Scan button*2
Custom button



Slots

Nano- SIM x 2,
Micro-SD Slot x 1,
(Reserved support eSIM)



Communication

5G/4G/3G/2G
Bluetooth: BT5.2 + BR/EDR + BLE
Wi-Fi: Wi-Fi 6E, 2.4G/5G
Support 2x2 MU-MIMO,
IEEE 802.11a/b/g/n/ac/d/e/h/i/k/r/v/w/ax
Roaming: 802.11r
(Over the Air);OKC;PMKID caching



Positioning

GPS
BEIDOU
GLONASS
Galileo



Protection

IP68
1.5m drop resistance



Environmental

Operating Temp.: -20 ~ +60°C
Storage Temp.: -40 ~ +70°C
Humidity: 5%RH ~ 95%RH(No condensation)
ESD: +/-15kv Air; +/-8kv contact

UROVO PTE. LIMITED

Website: en.urovo.com

Email: urovo@urovo.com

Address: 1 Raffles Place, #21-01 One Raffles Place Tower 1, Address: de Maas 9, 5684PL, Best, the Netherlands
Singapore 048616

Urovo Europe

Website: europe.urovo.com

Email: sales-europe@urovo-emea.com

LEXTER
People You Can Trust
www.lexter.com - info@lexter.com

*This page is subject to change
without prior notice