# Ulono





OB-11 PM P



00

NC

3

30

CE F©

# RT40S Industrial Mobile Computer

- Powered by Qualcomm octa-core 2.45 GHz processor and Android 13 system, delivering exceptional performance.
- A professional scan engine with a miximum scan range of 15 meters. Optional the version for cold chain, supports to work even at -30°C.
- Driven by Wi-Fi 6 and 2X2 MU-MIMO, network speed and throughput are nearly three times higher than previous generation.
- A 5200mAh removable smart battery with a management system that lowers power consumption, hot-swap battery design realizes battery replacement without reboot.





## **RT40S Industrial Mobile Computer**

### **Specifications**

### Urovo

¢	<b>Processor</b> Octa-core 2.45GHz	Ģ	<b>O.S.</b> Android 13.0,Upgradable to Android 17	Ð	<b>Memory</b> RAM: 4GB ROM: 64GB RAM: 8GB ROM: 128GB (Optional) Micro SD card, up to 256GB		Screen 4 inch 480*800 pixel	Ę,	Touch Screen Corning Gorilla Glass
	Dimensions	<u>-</u>	Scanning	」 シ	Audio		Battery	Ø	Camera
	Length: 199mm Width:58mm(handheld part) Most Thin part: 29mm Weight: 425g		Standard range scanner and extended range scanner are optional Support all industry-leading 1D/2D barcode on paper or screen		Receiver, speaker, microphone Support PTT (Push-to-Talk), speaker loudness over 100dB at 10cm		3.85V 5200mAh, Support hot swap	-	Rear camera: 13M pixel with flashlight
(	Buttons		Card slot	<b></b>	Communication	$\odot$	Positioning	$\widehat{}$	Protection
	38 keys 29 keys (optional) 51 keys (optional) Vol+/- button, Scan button*2, Custom button*1		Nano-SIM*1 PSAM/ SIM*1 (self-adaption)		4G, 3G, 2G BT 5.0+BR/EDR+BLE IEEE 802.11 a/b/g/n/ac/d/h/i/k/r/v/w/mc/ax, 2.4GHz/ 5GHz, Wi-Fi 6 (802.11ax); 2 x 2 MU-MIMO		GPS, Beidou, GLONASS, Galileo		IP68 dustproof and waterproof 1.8-meter resistance

### Pistol grip

Optional pistol grip with a scanning button

#### 💼 Sensors

Light + Accelerator+ Proximity + Geomagn+ Gyro

### **₿**<sup>≡</sup> Environment

Working temperature:  $-20^{\circ}C \sim +50^{\circ}C$ (cold chain version  $-30^{\circ}C \sim +50^{\circ}C$ ), Storage temperature:  $-40^{\circ}C \sim +70^{\circ}C$ Humidity: 5%RH -95%RH ESD:  $\pm 15kV$  air,  $\pm 8kV$  direct.

DISTRIBUTORE IN ITALIA

People You Can Trust

\*This page is subject to change without prior notice

#### **UROVO PTE. LIMITED**

Website: en.urovo.comUrovo EuropeEmail: urovo@urovo.comWebsite: europe.urovo.comAddress: 1 Raffles Place,Email: sales-europe@urovo-emea.com#21-01 One Raffles Place Tower 1, Singapore 048616Address: de Maas 9, 5684PL, Best, the Netherlands

www.lexter.com - info@lexter.com